

# 995LH

# RAPIDFLEX®



LOW HEADROOM, EXTREME EXTERIOR HIGH SPEED RUBBER DOOR



**SPECIALLY DESIGNED FOR APPLICATIONS WITH LOW HEADROOM. PERFECT FOR OLDER BUILDINGS AND UNDERGROUND ACCESS AREAS.**

- **Engineered for high cycles**
  - Springless design for minimal maintenance
  - Direct-mounted gear drive minimizes wear and tear
  - Variable frequency drive eliminates sudden jolts from door start/stop
- **Rugged construction** – Multi-reinforced rubber provides added strength without the weight
- **Perfect for exterior environments** – Multi-reinforced Nitrile Butadiene Rubber (NBR) provides resistance to petrochemicals adding strength without the weight
- **Compact, pre-installed header assembly** for low headroom applications standard
- **Optional programmable LED lighting system**
- **Standard hood** blocks moisture and debris from impeding door operation



**INDUSTRY EXPERTS,  
DELIVERING TOTAL SOLUTIONS**

# MODEL 995LH LOW HEADROOM, EXTREME EXTERIOR HIGH SPEED RUBBER DOOR

## Standard Features at a Glance

Maximum Width	22'
Maximum Height	10'
Headroom	12" for 8' to 14' wide doors 13" for 15' to 18' wide doors 15" for 19' to 22' wide doors
Maximum Opening Speed	Up to 30"/sec
Maximum Closing Speed	Up to 20"/sec
Breakaway Self Reset**	No
Wind Load*	Up to 27.0 psf
Curtain Material	5 layers of NBR Rubber with 4 layers of polyester weave
Curtain Lock	Yes
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device
Control Panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect
Obstruction Safety Detection	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50" - 54" from floor
Reversing Safety Edge	cUR 325 recognized wireless reversing monitored edge sensor with adjustable impact detection
Available Voltages	208V AC 3PH <sup>†</sup> , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH <sup>†</sup> ( <sup>†</sup> requires stand-alone mounted transformer)
Warranty	5-Year Limited

## Options

- **Actuation options** – Push button, key switch, pull switch, loop detector, motion detector, treadle switch, radio control. Wireless options available
- **Signaling device options** – Red/green LED warning light, horn/strobe combination, rotating warning light
- **Programmable LED lighting system** – 3' tall light bar with red, yellow, green lighting
- **20" high vision panels** – spaced evenly across width of door
- **Light Curtain** – Front or rear mounted; available in 3' or 6' models
- **Sealed Brake Kit** – For exterior mounted environments
- **Self-regulating gearbox heater** – For cold climates to ensure optimal performance

## Curtain Color Options



Black



Blue

Standard color for guides and bottom bar is yellow. Approximately 200 optional RAL powder coat colors are also available.



Actual colors may vary from brochure due to fluctuation in the printing process. **Always request a color sample from your Overhead Door™ Distributor for accurate color matching.**

\* Wind load is the ultimate pressure tested at door width of 19'.

\*\* Automatic reset not available with low headroom model.



Updated guide design allows for easy manual reset.



**INDUSTRY EXPERTS,  
DELIVERING TOTAL SOLUTIONS**



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067  
**1-800-929-DOOR • sales@overheaddoor.com**  
**overheaddoor.com**